

23180 CA/W33



/// V_{Cs} A

01


02

62

04

07

/// V_{Bs} D



⊖ V_{dsp}
 ∕ V_{dmp}
 ↗ K_{ia} B

↗ S_d G

⊖ V_{Dsp}
 ∕ V_{Dmp}
 ↗ K_{ea} C
 ∕ S_D A

- 1、Tolerance of running accuracy are according to relevant state standard;
- 2、The value of the basic group of radial clearance:min **** max ****;
- 3、Rated load: Cr= **** kN Cor= **** kN.

62	Guide ring		Steel 20—GB/T699						
07	Cage		Brass CuZn39Pb2-EN 1652:1997						
04	Roller		Steel 100CrMnSi6-4—ISO 683-17:1999						
02	Inner ring		Steel 100CrMnSi6-4—ISO 683-17:1999						
01	Outer ring		Steel 100CrMnSi6-4—ISO 683-17:1999						
No.	Designation	Qty	Material	unit	toatl	Remark			
				Weight (kg)					
Luoyang JCB Bearing Technology Co., Ltd Contact information Company Address : No. 285, Fenghua road, Luoyang, Henan, China. Postal code : 471000 Phone :86-379-68611678 Fax : 86-379-68611679 E-mail: sales@jcb-bearing.com Reserved E-mail: sales@sphericalrollerbearing.net Website: www.jcb-bearing.com www.sphericalrollerbearing.net			Spherical Roller Bearing	23180 CA/W33					
						Weight(kg)	Scale		
				S					——
				Total page 5		Page No. 1			
				Luoyang JCB Bearing Technology Co., Ltd					