



1. Tolerance of running accuracy are according to relevant state standard;
2. The value of the basic group of radial clearance: min 0.060 max 0.100 ;
3. Rated load: Cr=380 kN Cor=415 kN.

62	Guide ring	1	Steel 20—GB/T699		
07	Cage	2	Brass CuZn39Pb2—EN 1652:1997		
04	Roller		Steel 100CrMnSi6-4—ISO 683-17:1999		
02	Inner ring	1	Steel 100CrMnSi6-4—ISO 683-17:1999		
01	Outer ring	1	Steel 100CrMnSi6-4—ISO 683-17:1999		

No.	Designation	Qty	Material	unit	total	Remark
				Weight (kg)		

<p>Luoyang JCB Bearing Technology Co., Ltd</p> <p>Contact information</p> <p>Company Address : No. 285, Fenghua road, Luoyang, Henan, China.</p> <p>Postal code : 471000</p> <p>Phone :86-379-68611678</p> <p>Fax : 86-379-68611679</p> <p>E-mail: sales@jcb-bearing.com</p> <p>Reserved E-mail: sales@sphericalrollerbearing.net</p> <p>Website: www.jcb-bearing.com</p> <p>www.sphericalrollerbearing.net</p>	<h2>Spherical Roller Bearing</h2>	21318-E1-XL			
				Weight(kg)	Scale
		S		6.26	—
		Total page 5		Page No. 1	
Luoyang JCB Bearing Technology Co., Ltd					