



- 1, Tolerance of running accuracy are according to relevant state standard;
- 2, The value of the basic group of radial clearance: min 0.075 max 0.120 ;
- 3, Rated load: Cr=400 kN Cor=530 kN.

|    |            |   |                                    |  |  |
|----|------------|---|------------------------------------|--|--|
| 62 | Guide ring | 1 | Steel 20—GB/T699                   |  |  |
| 07 | Cage       | 2 | Brass CuZn39Pb2-EN 1652:1997       |  |  |
| 04 | Roller     |   | Steel 100CrMnSi6-4—ISO 683-17:1999 |  |  |
| 02 | Inner ring | 1 | Steel 100CrMnSi6-4—ISO 683-17:1999 |  |  |
| 01 | Outer ring | 1 | Steel 100CrMnSi6-4—ISO 683-17:1999 |  |  |

| No. | Designation | Qty | Material | unit        | total | Remark |
|-----|-------------|-----|----------|-------------|-------|--------|
|     |             |     |          | Weight (kg) |       |        |

|  |                                   |  |  |                  |  |            |       |
|--|-----------------------------------|--|--|------------------|--|------------|-------|
| <p>Luoyang JCB Bearing Technology Co., Ltd<br/>                 Contact information<br/>                 Company Address : No. 285, Fenghua road,<br/>                 Luoyang, Henan, China.<br/>                 Postal code : 471000<br/>                 Phone :86-379-68611678<br/>                 Fax : 86-379-68611679<br/>                 E-mail: sales@jcb-bearing.com<br/>                 Reserved E-mail: sales@sphericalrollerbearing.net<br/>                 Website: www.jcb-bearing.com<br/>                 www.sphericalrollerbearing.net</p> | <h2>Spherical Roller Bearing</h2> |  |  | 23022-E1-XL-TVPB |  |            |       |
|  |                                   |  |  |                  |  | Weight(kg) | Scale |
|  |                                   |  |  | S                |  | 3.55       | —     |
|  |                                   |  |  | Total page 5     |  | Page No. 1 |       |
| Luoyang JCB Bearing Technology Co., Ltd  |                                   |  |  |                  |  |            |       |