



1. Tolerance of running accuracy are according to relevant state standard;
2. The value of the basic group of radial clearance: min 0.075 max 0.120 ;
3. Rated load: Cr=710 kN Cor=870 kN.

62	Guide ring	1	Steel 20—GB/T699										
07	Cage	2	Brass CuZn39Pb2—EN 1652:1997										
04	Roller		Steel 100CrMnSi6-4—ISO 683-17:1999										
02	Inner ring	1	Steel 100CrMnSi6-4—ISO 683-17:1999										
01	Outer ring	1	Steel 100CrMnSi6-4—ISO 683-17:1999										
No.	Designation	Qty	Material	unit	total	Remark							
				Weight (kg)									
Luoyang JCB Bearing Technology Co., Ltd Contact information Company Address : No. 285, Fenghua road, Luoyang, Henan, China. Postal code : 471000 Phone :86-379-68611678 Fax : 86-379-68611679 E-mail: sales@jcb-bearing.com Reserved E-mail: sales@sphericalrollerbearing.net Website: www.jcb-bearing.com www.sphericalrollerbearing.net			<h2>Spherical Roller Bearing</h2>		<h1>23222-E1-XL-TVPB</h1>								
<table border="1" style="width: 100%;"> <tr> <td style="width: 20%;">S</td> <td style="width: 20%;"></td> <td style="width: 20%;"></td> <td style="width: 20%;">Weight(kg)</td> <td style="width: 20%;">Scale</td> </tr> <tr> <td></td> <td></td> <td></td> <td>9.18</td> <td>—</td> </tr> </table>		S					Weight(kg)	Scale				9.18	—
S			Weight(kg)	Scale									
			9.18	—									
Luoyang JCB Bearing Technology Co., Ltd													